

DETACK™

Stop the “STICK” on freshly applied sealant



Economical, time-saving, detackifying solution for hot pour sealant application

BENEFITS

- Applies over hot sealant
- Eliminates tracking & sticking
- Increases production
- Decreases labor cost
- Reduces traffic closure-time
- Protects sealant integrity



DETACK is an economical, biodegradable liquid that eliminates the surface tack on freshly applied hot pour sealant product. Applying DETACK is a one man operation that saves money, time and increases efficiency as there's no need to wait until the sealant has cooled before opening the pavement to traffic, and can be used in place of sand or toilet paper. If you're looking for economical, time-saving solutions then DETACK is your answer!

DETACK is supplied in a ready to use 5 gallon (19L) plastic pails. To use, DETACK is typically poured into pressurized hand pump garden sprayer. The spray pattern should be adjusted to a medium fan and should be applied to the sealant immediately after sealant is placed, or when surface tack is present.

Usage rate of DETACK is typically 1 gallon (3.8L) per 1000-2000 linear feet (305-610m) of sealed cracks. DETACK should be applied to cover the sealant surface with minimal excess of application onto pavement surface. The use of this product in no way supersedes the warnings and instructions provided with the sealant used. Read the Installation Instructions on the product container prior to use. DETACK is a water based product and should not be exposed to freezing temperatures.

CRAFCO®
INC
PRESERVATION PRODUCTS PAVEMENT
Delivering Confidence Through Innovation, Quality and Value Since 1976

©2016 Crafcoco, Inc. July #A1043

phone: (800) 528-8242 • email: sales@crafcoco.com • web: crafcoco.com