

READ BEFORE USING THIS PRODUCT

GENERAL: Crafcoc Gray Surface Dressing Aggregate is used as a topping for hot applied patching and pavement repair treatments in AC and PCC pavements. The Surface Dressing Aggregate provides aesthetic value to the repair as well as providing a skid resistance and surface protection.

PROPERTIES:

Properties of Crafcoc Gray Surface Dressing Aggregate are as follows:

Property	Specification
Color	Gray
Moisture (%)	0.5 maximum
Density (g/cm ³)	2.65 – 2.73
Sieve Analysis (ASTM C136, % passing)	
	¼"
	#4
	#16
	#30
	#200
	100
	99-100
	0-7
	0-2
	0-1

INSTALLATION: Gray Surface Dressing Aggregate is used as a topping to dress the surface of hot applied repair material installations. It may be applied by broadcasting by hand or machine while the repair material is still warm enough to allow the aggregate to adhere. Consult the Product Data Sheet and Installation Instructions of the Crafcoc product that the Gray Surface Dressing Aggregate is being used in conjunction with for specific usage details, coverage rates, application times and temperature conditions.

PACKAGING: Crafcoc Gray Surface Dressing Aggregate is supplied in bags. Each bag contains 50lb of material.

STORAGE: Bags of Gray Surface Dressing Aggregate must be stored in a dry location and be kept dry at all times. Wet or damp Gray Surface Dressing Aggregate is not acceptable for use, since it may not adhere properly. Gray Surface Dressing Aggregate shall be thoroughly dry prior to use.

SAFETY PRECAUTIONS: Before use, the crew should read and understand product safety information contained in the SDS, which is supplied with each shipment. The SDS describes the characteristics of the product as well as any potential health hazards and precautions for safe handling and use.

WARRANTY Crafcoc, Inc. warrants that Crafcoc products meet applicable ASTM, AASHTO, Federal or State specifications at time of shipment. Techniques used for the preparation of pavement surfaces prior to product installation are beyond our control as are the use and application of the product; therefore, Crafcoc shall not be responsible for improperly applied or misused products. Remedies against Crafcoc as agreed to by Crafcoc, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafcoc, Inc. All claims for breach of this warranty must be made within three (3) months of the date of use or twelve (12) months from the date of delivery by Crafcoc whichever is earlier. There shall be no other warranties expressed or implied.