

Detack™



Stop the stick on freshly applied sealant

Detack™ is an economical, biodegradable liquid that immediately eliminates the surface tack on freshly applied hot pour sealant. Applying Detack is a one-person operation that saves time and increases efficiency because there's no need to wait until the sealant has cooled before opening the pavement to traffic. It's great for use in intersections, in front of driveways and business entrances to keep work zones closed for shorter times. Avoid messes by using Detack in place of sand or toilet paper. If you're looking for economical, time-saving solutions then Detack is your answer!

BENEFITS

Applies directly over hot sealant

Eliminates tracking & sticking

Reduces traffic closure-time

Protects sealant integrity





Open to Traffic Immediately

**Economical,
time-saving,
Detackifying
solution for hot
pour sealants.**

How it Works

Detack is supplied in a ready to use 5 gallon (19L) plastic pails. To use, Detack is typically poured into a hand-pump garden sprayer. The spray pattern should be adjusted to a medium fan and should be applied to the sealant immediately after sealant is placed, or when surface tack is present.

Recommended Usage

Usage rate of Detack is typically 1 gallon (3.8L) per 1000-2000 linear feet (305-610m) of sealed cracks. Detack should be applied to cover the sealant surface with minimal excess of application onto pavement surface. Read the Installation Instructions on the product container prior to use. Detack is a water-based product and should not be exposed to freezing temperatures.

Save time, money and frustration with Detack and don't look back.



Scan this QR code to view
all of CrafcO's material
documentation.



©September 2025 CrafcO, Inc.