



SPECIFICATIONS

56700 PATCHER II™ (200 GAL) DIESEL-FUELED

6165 W Detroit St. • Chandler AZ 85226
 +1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513
 www.crafco.com

JANUARY 2017

The purpose of these specifications is to describe a double-boiler type mixer that is specifically designed for and shall be capable of heating and melting Crafco TechCrete, Mastic One, Matrix 501 and PolyPatch products. All qualified bidders must have and maintain a complete inventory of repair parts and have experienced factory-trained service personnel for this equipment.

	<u>Comply</u>	<u>Does Not Comply</u>
1. GENERAL		
A. This machine shall be the manufacturer's current production model manufactured in the United States of America.	_____	_____
B. The machine will be capable of starting at ambient temperature and be ready for operation in one and a half hours or less.	_____	_____
C. A comprehensive safety manual and an operational/maintenance manual shall be supplied with each unit.	_____	_____
D. Thermostatic control for the heat transfer medium shall be provided and shall have sufficient sensitivity to maintain product temperature within the manufacturer's specified application temperature range.	_____	_____
E. Temperature indicating devices shall have intervals no greater than 5°F (2.8°C) and shall be calibrated as required to assure accuracy.	_____	_____
F. The mixer shall have a continuous material mixing system to provide uniform viscosity and temperature of material being applied.	_____	_____
2. REQUIRED SAFETY FEATURES		
A. The unit shall have a safety shut-off on the lid that automatically stops the agitator when the lid is opened.	_____	_____
B. This unit shall have a safety chain in place to prevent accidental discharge of material.	_____	_____
C. The unit shall be oil jacketed to ensure safe heating and handling of materials. Direct fire and air jacketed units are not acceptable.	_____	_____
D. The heat transfer oil shall adequately and efficiently bring the material to application temperature without the use of a heat transfer oil circulation pump. This eliminates the potential exposure of personnel to pressurized hot transfer oil.	_____	_____
E. All fluid tanks shall be located and mounted above the top of the trailer frame to prevent exposure and damage.	_____	_____
F. Other _____	_____	_____
	_____	_____

<u>Comply</u>	<u>Does Not Comply</u>
---------------	------------------------

3. TOWING FRAME AND JACK

- | | | |
|---|-------|-------|
| A. This machine shall be trailer mounted. | _____ | _____ |
| B. The longitudinal side frames and tongue members of the trailer shall be on one continuous piece construction composed of hot rolled steel channel having the minimum dimensions of 5 inches (12.70 cm) web, 3/16 inch (.48 cm) thickness with 1.75 inch (4.5 cm) flanges. | _____ | _____ |
| C. The configuration of the channels shall be cold formed with the flanges on the outside resulting in a one-piece frame member with no cross welding of or on the flanges to avoid any possibility of flange stress cracking. | _____ | _____ |
| D. The tongue shall be equipped with an appropriate heavy pintle hitch, and shall be adjustable in height above ground level from a minimum of 14 inches (35.6 cm), to a maximum of 32 inches (81.3cm), permitting practically level towing with a wide range of towing vehicles. | _____ | _____ |
| E. The towing hitch shall be bolted to the hitch plate for easy height adjustment and/or conversion to other type hitches. | _____ | _____ |
| F. A screw-post tongue jack shall be a heavy duty type with a load capacity of 5,000 pounds (2,268 kg) and it shall be side mounted and swing away for positive road clearance while under tow. | _____ | _____ |
| G. Other _____
_____ | _____ | _____ |

4. RUNNING GEAR

- | | | |
|--|-------|-------|
| A. The unit shall be equipped with a dual independent rubber torsional suspension having a safe load capacity of 9,900 pounds (4,491 kg), electric brakes, modular disc wheels and ST225 R75 - 15 tubeless tires (Load Range D). | _____ | _____ |
| B. This suspension eliminates springs and shackles that rust and reduce ground clearance. | _____ | _____ |
| C. The trailer shall have dual taillights, stop lights and turn signals. | _____ | _____ |
| D. Lights shall be ICC approved. | _____ | _____ |
| E. A license plate holder shall be attached to the rear of trailer as well. | _____ | _____ |
| F. The unit shall also be equipped with two safety chains not less than 48 inches (121.9cm) of .38 inch (.97 cm) coil proof chain, attached to the tongue with a drilled type clevis pin on the end attached to the frame and screw type clevis pin on the opposite end. | _____ | _____ |
| G. Total shipping weight is approximately 5,300 pounds (2404 kg). | _____ | _____ |

	<u>Comply</u>	<u>Does Not Comply</u>
H. Other _____ _____	_____	_____

5. HEATING TANK

A. The material heating tank shall be a U- shaped vessel with 17 inch (86 cm) radius by 48 inches (122 cm) long having a capacity of 200 gallons (757 L) at ambient temperature.	_____	_____
B. The tank will have a rear discharge with a minimum opening of 42 square inches, which drops material onto an 8 inch long spout.	_____	_____
C. The minimum height from the bottom of the spout to the ground shall be 19 inches to allow use of a material handler or optional material chutes.	_____	_____
D. A double boiler type jacket shall create a reservoir that shall hold a minimum of 35 gallons (132 L) of heat transfer oil at 70°F (21.1°C). (Note: at 500°F (260°C) the heating oil will expand approximately 18%)	_____	_____
E. The jacket shall wrap around 100% of the outside area of the material tank including the sides, front, back and bottom and allow for complete circulation of the heated transfer oil.	_____	_____
F. The tank and jacket shall be made of not less than 0.1875 inch (0.476 cm) hot roll steel.	_____	_____
G. There shall be one plug to allow the entire heat transfer oil system to be drained.	_____	_____
H. The heat transfer oil shall be ISO grade 68.	_____	_____
I. The heating tank shall be insulated with a minimum of 1.5 inch (3.81 cm) thick high temperature ceramic insulation and covered by a 12 gauge (0.27 cm) steel outer wrapper.	_____	_____
J. Fiberglass or rock wool insulation is unacceptable due to their moisture retention properties resulting in a significant loss of their insulating value over an eighteen-month period.	_____	_____
K. Tank shall have two (2) 1500 watt-110 volt electric overnight heaters.	_____	_____
L. Other _____ _____	_____	_____

6. EXPANSION TANK

A. A vented expansion tank for heat transfer oil shall be provided.	_____	_____
B. Other _____ _____	_____	_____

<u>Comply</u>	<u>Does Not Comply</u>
---------------	----------------------------

7. HYDRAULIC SYSTEM

- | | | |
|--|-------|-------|
| A. The hydraulic system shall incorporate a hydraulic pump to power the mixer. | _____ | _____ |
| B. Mixer valve shall be solenoid operated by toggle switch located on the burner control box. | _____ | _____ |
| C. The control will allow for bi-directional operation of the mixer. | _____ | _____ |
| D. A flow control valve will be mounted by the burner control box to allow the operator to adjust the mixer operating speed. | _____ | _____ |
| E. The minimum 15 gallon (57 L) hydraulic tank will be equipped with an internal 10-micron full flow filter. | _____ | _____ |
| F. The filter shall be equipped with a restriction indicator to indicate the need for service. | _____ | _____ |
| G. Other _____
_____ | _____ | _____ |

8. INSULATION

- | | | |
|---|-------|-------|
| A. The heating tank shall be insulated with a minimum of 1-½ inch (3.81 cm) thick high temperature ceramic insulation and covered by a 12 gauge (.27 cm) steel outer wrapper. | _____ | _____ |
| B. Fiberglass or rock wool insulation is unacceptable due to their moisture retention properties resulting in a significant loss of their insulating value over an eighteen-month period. | _____ | _____ |
| C. Other _____
_____ | _____ | _____ |

9. LOADING HATCH

- | | | |
|--|-------|-------|
| A. One low profile opening for loading shall be required. | _____ | _____ |
| B. The loading height shall not exceed 61.5 inches (156 cm). | _____ | _____ |
| C. The opening shall have a minimum area of 384 square inches (2477 square cm). | _____ | _____ |
| D. One opening shall be equipped with a permanent grated internal cover plate suitable to store a material bucket to allow draining back into the material tank. | _____ | _____ |
| E. Each lid shall have a latching system to prevent accidental opening. | _____ | _____ |
| F. Other _____
_____ | _____ | _____ |

Comply Does Not Comply

10. HEATING SYSTEM

- A. The heat transfer oil is heated by a 370,000 BTU diesel burner at the bottom of the heat transfer oil tank. _____
- B. The total area exposed to the burner shall be a minimum of 5,941 square inches (38,328 square cm). _____
- C. The material tank shall have a minimum of 5,736 square inches (37,006 square cm) of contact with the heat transfer oil. _____
- D. No other mechanical circulation of the heat transfer oil by a pump shall be accepted. _____
- E. Other _____

11. IGNITION OF BURNER

- A. The burner shall be lit by a constant duty high voltage transformer powering an electric spark igniter. _____
- B. This igniter shall work in conjunction with a sensor that detects a lack of burn or ignition and shuts down the fuel supply. _____
- C. The thermostat control is located on the curbside of the machine for operator safety. _____
- D. Other _____

12. TEMPERATURE CONTROL

- A. The mixer shall have a thermostatic control device that will automatically regulate hot oil and material temperature. _____
- B. The control shall have a digital readout for temperatures of hot oil and material. _____
- C. The thermostat shall control burner ignition for a material temperature range from a low of 200°F (93.3°C) up to a high of 450°F (232.2°C). _____
- D. The hot oil temperature range shall be from a low of 150°F (65.5°C) up to a high of 550°F (287.7°C). _____
- E. The controls shall be activated by a single power switch. _____
- F. All temperature controls shall be contained in a single weatherproof control box. _____
- G. Other _____

<u>Comply</u>	<u>Does Not Comply</u>
---------------	------------------------

13. DRIVE AND DRIVE CONTROLS

- | | | |
|--|-------|-------|
| A. The motive force to the mixer shall be a hydraulic motor driven by a single hydraulic pump. | _____ | _____ |
| B. The drive control governing the rotational direction of the mixer shall be controlled by a solenoid operated hydraulic control valve. | _____ | _____ |
| C. The valve is electrically actuated by a toggle switch on the burner control panel and can be reversed as required. | _____ | _____ |
| D. A flow control valve can be used to adjust mixer rotational speed. | _____ | _____ |
| E. The hydraulic tank will be equipped with an internal 10-micron full flow filter that includes an indicator to indicate the need for service. | _____ | _____ |
| F. A sight level indicator equipped with a thermometer to measure oil temperature will be mounted on the tank and located where it is easily viewed. | _____ | _____ |
| G. Other _____
_____ | _____ | _____ |

14. AGITATION

- | | | |
|---|-------|-------|
| A. The material shall be mixed by a hydraulically driven, full sweep horizontal mixer shaft with four opposing V- shaped paddles. | _____ | _____ |
| B. This feature ensures that material remains in complete suspension. | _____ | _____ |
| C. The mixer shaft shall be coupled from a 6 to 1 gearbox reducer to the hydraulic motor capable of 400 ft. lbs. of torque. | _____ | _____ |
| D. The mixer rotates in both directions. | _____ | _____ |
| E. For additional safety the mixer will shut off automatically when the loading hatch is opened. | _____ | _____ |
| F. Other _____
_____ | _____ | _____ |

15. ENGINE

- | | | |
|---|-------|-------|
| A. The unit shall be equipped with a diesel engine complying with the following specifications:
Electric Start
Three cyl. 19hp (14.2 kw) @ 3000 RPM, Tier 4 Final Emissions
Full Flow Oil Filter
Water cooled | _____ | _____ |
| B. The melter shall have a 26 gallon (98.4 L) diesel fuel tank for operation of the entire unit. | _____ | _____ |
| C. Other _____
_____ | _____ | _____ |

<u>Comply</u>	<u>Does Not Comply</u>
---------------	------------------------

16. TOOL HEATING BOX AND TOOLS

- | | | |
|---|-------|-------|
| A. The tool heating box shall be 26 inches (66 cm) in height, 14 inches (35.5 cm) in width, and 18 inches (46.4 cm) long. | _____ | _____ |
| B. The tool heating box shall be constructed of not less than 0.105 (0.267 cm) HRS outer skin, be insulated with a minimum of 1 inch (2.5 cm) thick high temperature ceramic insulation and have 0.06 (.15 cm) stainless steel inner liner. | _____ | _____ |
| C. Fiberglass or rock wool insulation is unacceptable due to their moisture retention properties resulting in a significant loss of their insulating value over an eighteen-month period. | _____ | _____ |
| D. The diesel burner shall be bolted to the side of a combustion chamber and the tool heating box is welded to the top of this chamber. | _____ | _____ |
| E. The burner shall have a minimum of 82,000 BTU supplied by a 12Vdc burner. | _____ | _____ |
| F. The burner shall be controlled by an "On" – "Off" switch located at the rear of the machine. | _____ | _____ |
| G. Tools included shall be: Two (2) each ironing wands, One (1) each chute scraper, One (1) each tank scraper, Two (2) each metal coal buckets. | _____ | _____ |
| H. Other _____
_____ | _____ | _____ |

17. PAINT

- | | | |
|---|-------|-------|
| A. All painted surfaces shall be coated with two-part epoxy primer and two-part urethane paint applied by trained painters. | _____ | _____ |
| B. Other _____
_____ | _____ | _____ |

18. MISCELLANEOUS

- | | | |
|--|-------|-------|
| A. There shall be a gate valve at the rear of the machine. | _____ | _____ |
| B. Other _____
_____ | _____ | _____ |

<u>Comply</u>	<u>Does Not Comply</u>
---------------	------------------------

19. TRAINING

- | | | |
|--|-------|-------|
| A. An authorized, factory-trained representative will be made available for a full day of training at a facility designated by the bidding agency. | _____ | _____ |
| B. At this training session a complete operational, mechanical and safety overview will occur. | _____ | _____ |
| C. Both safety and operational manuals will be viewed and discussed with all concerned personnel. | _____ | _____ |
| D. Additionally, the representative will be available at that time for "on the job" safety and field training. | _____ | _____ |
| E. Other _____
_____ | _____ | _____ |

20. SAFETY AND TRAINING MANUALS

- | | | |
|--|-------|-------|
| A. A written Safety Manual will be provided to the bidding agency. | _____ | _____ |
|--|-------|-------|

21. PARTS

- | | | |
|---|-------|-------|
| A. Bidders must show proof that a large stock of parts for the model of equipment upon which he is bidding is maintained at his facility. | _____ | _____ |
|---|-------|-------|

22. AWARD

- | | | |
|---|-------|-------|
| A. Equipment is for use by the Highway Department and must meet the requirements of that agency as interpreted by the Highway Commissioner. | _____ | _____ |
| B. Prior to award the Purchasing Agency may require a visit to the supplier's facility to assure supplier has plant capacity to manufacturer and deliver equipment on time as required. | _____ | _____ |
| C. If it is determined that the supplier cannot supply as requested, this is just cause for cancellation. | _____ | _____ |

23. WARRANTY

- | | | |
|---|-------|-------|
| A. The manufacturer shall warranty the equipment for one year or as otherwise noted in the manufacturer's standard warranty policy. | _____ | _____ |
|---|-------|-------|

24. QUALIFICATIONS OF BIDDERS

- | | | |
|--|-------|-------|
| A. No bid will be considered unless the bidder can meet the following conditions: | _____ | _____ |
| B. Bidder must have a parts/service location and keeps a sufficient stock of parts on hand at all times. | _____ | _____ |
| C. The equipment offered is a stock model chassis that meets the requirements of the specifications without material changes or modifications. | _____ | _____ |

- | | <u>Comply</u> | <u>Does Not Comply</u> |
|---|---------------|------------------------|
| D. The model is regularly advertised and sold by the manufacturer. | _____ | _____ |
| E. The bidder has been engaged in the sale and support of this make and model of equipment for at least twenty-four months. | _____ | _____ |

OPTIONS (X if to be included):

- _____ Removable Material Chute
 The material chute shall be minimum 37 inches (93.98 cm) in length by 8 inches (20.3 cm) in width by 4 inches (10.2) in depth with a steel thickness of 0.1345 inches (0.34 cm). To aid in placement of material from machine directly into repair area.
- _____ Propane Torch and Bottle
 30 lb. bottle with regulator, 500,000 BTU propane hand torch with 20 foot (6.1 meter) hose.
- _____ Heated (heat transfer oil) Removable Material Chute
 The heat transfer oil heated material chute shall be minimum 37 inches (93.98 cm) in length by 8 inches (20.3 cm) in width by 4 inches (10.2) in depth with a steel thickness of 0.1345 inches (0.34 cm). A hydraulic driven 1.5 GPM heat transfer oil pump will circulate the oil from the heat transfer oil tank into the heated chute and back into the heat transfer oil tank. The heated chute shall pivot under the material drain and be easily removable. The heat transfer oil lines going to the chute shall have swivels and be insulated to protect the machine operators from burns. There shall be shut off valves on the heat transfer oil lines between the chute and the tank.
- _____ Hot Mastic Applicator
 For handling and distributing of PolyPatch material from the Patcher to the repair area. Propane heated with material side discharge gate.
- _____ Shoe Boxes (various sizes):
- | | |
|-------------------------------|----------------------------------|
| _____ Deep Small 8 X 8 X 6 | _____ Shallow Small 8 X 8 X 3 |
| _____ Deep Medium 8 X 10 X 6 | _____ Shallow Medium 8 X 10 X 3 |
| _____ Deep Large 8 X 12 X 6 | _____ Shallow Large 8 X 12 X 3 |
| _____ Deep X Large 8 X 14 X 6 | _____ Shallow X Large 8 X 14 X 3 |
- _____ Center Drag Boxes (Non-heated or Heated Material Chute is required for use)
- | | |
|----------------|---------------|
| _____ 10" Wide | _____ 3' Wide |
| _____ 24" Wide | _____ 4' Wide |
- _____ 2 ½ Inch Pintle Hitch
- _____ 3 Inch Pintle Hitch
- _____ Hot Air Lance
- _____ Extra Hydraulic Filter
- _____ Fire Extinguisher mounted on the Trailer
- _____ Tool Box
- _____ Custom Paint
- _____ Engine Cover
- _____ Surge Brakes
- _____ Mast Mounted Strobe Light, Class II.
- _____ Mast Mounted Strobe Light, Class I/CA Title 13
- _____ Rear Work Light
- _____ Hitch Extension, 28"
- _____ Hitch Extension, 39"

APPROVED EQUAL

The approved make and model for this specification is a Crafcro Patcher II. Bidders offering to supply other than the approved make and model must supply a detailed description of the equipment being offered. Bidders offering to supply equipment other than the approved make and model shall also supply a list of references of who have successfully heated, mixed and applied Crafcro TechCrete, Mastic One, Matrix 501 and PolyPatch through the equipment being offered. For purposes of comparison a separate list of all deviations to this specification must be attached to your bid document.

Prior to bid award an on-site demonstration of the equipment offered may be requested. All bidders offering other than the approved model listed will be required to provide an on-site demonstration to verify that their unit complies with all specification requirements before their bid will be considered.

Failure to carry out the provisions noted herein is deemed sufficient reason to reject the bidder's proposal.