CRAFCO INC

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or Crafco Roadsaver Silicone NS Sealant, Roadsaver Silicone SL, Roadsaver Silicone SL Ultra-Low

designation of the mixture Modulus

Registration number -

Synonyms None. **Issue date** 05-08-2020

Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pavement Joint Sealant

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Manufacturer: Crafco, Inc.

Address: 6165 West Detroit St.

Chandler, AZ 85226 USA

Contact Name: Crafco Materials Engineering

Telephone: 602-276-0406 **E-mail:** sales@crafco.com

CHEMTREC: 800-424-9300 (North America)

+ 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Reproductive toxicity Category 2 H361 - Suspected of damaging

fertility or the unborn child.

Environmental hazards

Hazardous to the aquatic environment,

Category 2

H411 - Toxic to aquatic life with

long lasting effects.

Hazard summary Not available.

long-term aquatic hazard

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Toluene

Hazard pictograms



Signal word Warning

Hazard statements

H361 Suspected of damaging fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection

Response

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P391 Collect spillage.

Material name: Crafco Roadsaver Silicone NS Sealant, Roadsaver Silicone SL, Roadsaver Silicone SL Ultra-Low Modulus 5012 Version #: 01 Issue date: 05-08-2020

Storage

P405 Store locked up.

Disposal

See section 13 of this SDS for disposal instructions.

Dispose of contents/container in accordance with local/regional/national/international regulations P501

Supplemental label

56,88% of the mixture consists of component(s) of unknown acute oral toxicity. 59,25% of the information mixture consists of component(s) of unknown acute inhalation toxicity. 61,62% of the mixture

consists of component(s) of unknown acute hazards to the aquatic environment. 40,29% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No. R	EACH Registration No.	Index No.	Notes
Polydimethylsiloxane	15 - 40	9016-00-6	-	-	
		-			
Classification:	Aquatic Chronic 2;H411				
Toluene	0 - 2	108-88-3	-	601-021-00-3	#
		203-625-9			
Classification:	Flam. Liq. 2;H225, Asp	. Tox. 1;H304, Skin Irrit	:. 2;H315, STOT SE 3;H33	6, STOT RE	
	2;H373, Aquatic Chroni	c 2;H411		•	

Other components below reportable

levels

SECTION 4: First aid measures

General information If you feel unwell, seek medical advice (show the label where possible). Keep victim warm. Keep

victim under observation. Ensure that medical personnel are aware of the material(s) involved, and

take precautions to protect themselves. Wash contaminated clothing before re-use.

4.1. Description of first aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact IF ON SKIN: Gently wash with plenty of soap and water. If irritation persists get medical attention.

Eye contact Immediately rinse with water for several minutes. Get medical attention if irritation develops and

Ingestion Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any

immediate medical attention and special treatment

needed

Not available

Keep victim warm. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

Water. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Irritating, corrosive and/or toxic gases or fumes will be released during a fire.

5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material

unless wearing appropriate protective clothing.

For emergency responders

Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental

precautions

Avoid release to the environment.

6.3. Methods and material for Eliminate sources of ignition. Dike far ahead of spill for later disposal. Following product recovery, containment and cleaning up flush area with water.

6.4. Reference to other

sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe

handling

Avoid contact with skin, eyes and clothing. Do not ingest. Wash hands after handling and before eating. When using, do not eat, drink or smoke. Avoid contact during pregnancy/while nursing.

Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool and well-ventilated place.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	Туре	Value	Form
Silica (CAS 112945-52-5)	MAK	4 mg/m3	Inhalable fraction
TOLUENE (CAS 108-88-3)	MAK	190 mg/m3	
		50 ppm	
	STEL	380 mg/m3	
		100 ppm	
Belgium. Exposure Limit Values			

Components	Туре	Value
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3
		100 ppm
	TWA	77 mg/m3
		20 nnm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Туре	Value	Form
Silica (CAS 112945-52-5)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3	
		100 ppm	
	TWA	192 mg/m3	
		50 ppm	

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine,

Components	Туре	Value	Form
Silica (CAS 112945-52-5)	MAC	6 mg/m3	Total dust.
		2,4 mg/m3	Respirable dust.
TOLUENE (CAS 108-88-3)	MAC	192 mg/m3	
		50 ppm	
	STEL	384 mg/m3	

Material name: Crafco Roadsaver Silicone NS Sealant, Roadsaver Silicone SL, Roadsaver Silicone SL Ultra-Low Modulus 5012 Version #: 01 Issue date: 05-08-2020

	TWA	81 mg/m3
		25 ppm
France. Threshold Limit Components	t Values (VLEP) for Occupational Exp Type	osure to Chemicals in France, INRS ED 984 Value
TOLUENE (CAS 108-88-3)	VLE	384 mg/m3
Regulatory status:	Regulatory binding (VRC)	
		100 ppm
Regulatory status:	Regulatory binding (VRC)	
	VME	76,8 mg/m3
Regulatory status:	Regulatory binding (VRC)	
		20 ppm
Regulatory status:	Regulatory binding (VRC)	

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical

Components Components	rg) Type	Value	Form
Silica (CAS 112945-52-5)	TWA	4 mg/m3	Inhalable fraction.
TOLUENE (CAS 108-88-3)	TWA	190 mg/m3	
		50 ppm	
Germany. TRGS 900, Limit Value Components	s in the Ambient Air at the W Type	orkplace Value	Form
Silica (CAS 112945-52-5)	AGW	4 mg/m3	Inhalable fraction.

Components	es in the Ambient Air at the Workplace Type	Value	Form
TOLUENE (CAS 108-88-3)	AGW	190 mg/m3	
		50 ppm	
Greece. OELs (Decree No. 90/19	999, as amended)		
Components	Туре	Value	
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3	
		100 ppm	
	TWA	192 mg/m3	
		50 ppm	
Hungary. OELs. Joint Decree on Components	Chemical Safety of Workplaces Type	Value	
TOLUENE (CAS 108-88-3)	STEL	380 mg/m3	
(0.0000000)	TWA	190 mg/m3	
Iceland. OELs. Regulation 154/ Components	1999 on occupational exposure limits	Value	
•	Туре		
TOLUENE (CAS 108-88-3)	STEL	188 mg/m3	
	T\\(\alpha\)	50 ppm	
	TWA	94 mg/m3	
		25 ppm	
Ireland. Occupational Exposure Components	Limits Type	Value	Form
Silica (CAS 112945-52-5)	TWA	6 mg/m3	Total inhalable dust
		2,4 mg/m3	Respirable dust.
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3	
		100 ppm	
	TWA	192 mg/m3	
		50 ppm	
Italy. Occupational Exposure Li	mits		
Components	Туре	Value	
TOLUENE (CAS 108-88-3)	TWA	192 mg/m3	
		50 ppm	
Latvia. OELs. Occupational expo	osure limit values of chemical substanc	es in work enviro	onment
Components	Туре	Value	
Silica (CAS 112945-52-5)	TWA	1 mg/m3	
TOLUENE (CAS 108-88-3)	STEL	150 mg/m3	
		40 ppm	
	TWA	50 mg/m3	
		14 ppm	
Lithuania. OELs. Limit Values fo	or Chemical Substances, General Requi Type	rements Value	
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3	
		100 ppm	
	TWA	192 mg/m3	
		50 ppm	
Luxembourg. Binding Occupation Components	onal exposure limit values (Annex I), M Type	lemorial A Value	
Components	Туре	Value	

50 ppm

Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP.
424), Schedules I and V)

Components	Туре	Value	
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3	
		100 ppm	
	TWA	192 mg/m3	
		50 ppm	
Netherlands. OELs (binding)			
Components	Туре	Value	
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3	
	TWA	150 mg/m3	
Norway. Administrative Norms fo	r Contaminants in the Work	olace	
Components	Туре	Value	Form
Silica (CAS 112945-52-5)	TLV	1,5 mg/m3	Respirable dust.
TOLUENE (CAS 108-88-3)	TLV	94 mg/m3	
		25 ppm	

Components	Туре	Value	
TOLUENE (CAS 108-88-3)	STEL	200 mg/m3	
	TWA	100 ma/m3	

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	туре	value
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3
		100 ppm
	TWA	192 mg/m3
		50 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) **Components Type** Value

TOLUENE (CAS 108-88-3) TWA 20 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace **Components** Value **Type**

Polydimethylsiloxane (CAS 9016-00-6)	STEL	300 mg/m3
	TWA	200 mg/m3
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3
		100 ppm
	TWA	192 mg/m3
		50 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents **Value Components Type**

	/ F -		
Silica (CAS 112945-52-5)	TWA	0,3 mg/m3	
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3	
		100 ppm	
	TWA	192 mg/m3	
		50 ppm	

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while

working (Official Gazette of the Components	Туре	Value	Form	
Silica (CAS 112945-52-5)	TWA	4 mg/m3	Inhalable fraction	
TOLUENE (CAS 108-88-3)	TWA	192 mg/m3		
		50 ppm		
Spain. Occupational Exposure L	imits			
Components	Туре	Value		
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3		
		100 ppm		
	TWA	192 mg/m3		
		50 ppm		
Sweden. OELs. Work Environmo Components	ent Authority (AV), Occupatio Type	onal Exposure Limit Values Value	(AFS 2015:7)	
TOLUENE (CAS 108-88-3)	Ceiling	384 mg/m3		
		100 ppm		
	TWA	192 mg/m3		
		50 ppm		
Switzerland. SUVA Grenzwerte Components	am Arbeitsplatz Type	Value		
TOLUENE (CAS 108-88-3)	STEL	760 mg/m3	760 mg/m3	
		200 ppm		
	TWA	190 mg/m3		
		50 ppm		
JK. EH40 Workplace Exposure	Limits (WELs)			
Components	Туре	Value	Form	
Silica (CAS 112945-52-5)	TWA	6 mg/m3	Inhalable dust.	
		2,4 mg/m3	Respirable dust.	
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3		
		100 ppm		
	TWA	191 mg/m3		
		50 ppm		
EU. Indicative Exposure Limit V Components	alues in Directives 91/322/E Type	EC, 2000/39/EC, 2006/15, Value	/EC, 2009/161/EU	
TOLUENE (CAS 108-88-3)	STEL	384 mg/m3		
		100 ppm		
	TWA	192 mg/m3		

Biological limit values

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended) Specimen Sampling Time Determinant

Components	value	Determinant	Specimen	Sampling Time	
TOLUENE (CAS 108-88-3)	2,5 g/g	Hippuric acid	Creatinine in urine	*	
	1 mg/g	o-Cresol	Creatinine in urine	*	
	1 mg/l	Toluene	Blood	*	
	1,05 mmol/mol	o-Cresol	Creatinine in urine	*	
	1,58 mol/mol	Hippuric acid	Creatinine in urine	*	
	20 ppm		End-exhaled air	*	

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)

Components	Value	Determinant	Specimen	Sampling Time	•
	10,85 umol/l	Toluene	Blood	*	
	0,83 umol/l		End-exhaled	*	

 $[\]ensuremath{^*}$ - For sampling details, please see the source document.

Czech Republic. Limit Values for Indictators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.

Components	Value	Determinant	Specimen	Sampling Time
TOLUENE (CAS 108-88-3)	1000 µmol/mmol	Hippuric acid	Creatinine in urine	*
	1600 mg/g	Hippuric acid	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV), Social Affairs and Ministry of Health Components Value Determinant Specimen Sampling Time TOLUENE (CAS 108-88-3) 500 nmol/l Toluene concentration Blood *

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065) Components Value Determinant Specimen Sampling Time

Components	value	Determinant	Specimen	Sampling Time
TOLUENE (CAS 108-88-3)	2500 mg/g	Acide hippurique	Creatinine in urine	*
	2500 mg/g	Acide hippurique	Creatinine in urine	*
	1 mg/l	Toluène	Venous blood	*

^{* -} For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time	
TOLUENE (CAS 108-88-3)	600 µg/l	Toluol	Blood	*	
	1,5 mg/l	o-Kresol (nach Hydrolyse)	Urine	*	

^{* -} For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling Time
TOLUENE (CAS 108-88-3)	1 mg/g	o-crezol	Creatinine in urine	*
	1,05 µmol/mmol	o-crezol	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling Time	
TOLUENE (CAS 108-88-3)	600 µg/l	Toluene	Blood	*	
	1600 mg/g	Hippuric acid	Creatinine in urine	*	
	1,03 mg/g	o-Cresol	Creatinine in urine	*	
	2401 mg/l	Hippuric acid	Urine	*	
	1,5 mg/l	o-Cresol	Urine	*	

^{* -} For sampling details, please see the source document.

^{* -} For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4					
Components	Value	Determinant	Specimen	Sampling Time	
TOLUENE (CAS 108-88-3)	0,6 mg/l	o-Cresol	Urine	*	
	0,05 mg/l	Tolueno	Blood	*	

* - For sampling details, please see the source document.

Switzerland, BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time
TOLUENE (CAS 108-88-3)	600 μg/l	Toluol	Blood	*
	2 g/g	Hippursäure	Creatinine in urine	*
	0,5 mg/l	o-Kresol	Urine	*

^{* -} For sampling details, please see the source document.

Recommended monitoring

Not available.

procedures

Not available. **Derived no effect levels**

(DNELs)

Not available. **Predicted no effect**

concentrations (PNECs)

Exposure guidelines

EU Exposure Limit Values: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Toluene (CAS 108-88-3) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering Provide adequate ventilation if fumes or vapors are generated.

controls

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Keep working clothes separately.

Eye/face protection Goggles/face shield are recommended.

Skin protection

- Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

- Other Wear appropriate chemical resistant clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not available.

When using, do not eat, drink or smoke. Use good industrial hygiene practices in handling this **Hygiene measures**

material. Wash hands before breaks and immediately after handling the product.

Environmental exposure Environmental manager must be informed of all major spillages. Avoid release to the aquatic

controls environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Paste. **Physical state** Liquid. Paste. **Form** Color Grey. Odor Sliaht. **Odor threshold** Not available. Not available.

Melting point/freezing point Not available.

Initial boiling point and

< 150 °F (< 65,56 °C)

boiling range

Flash point > 392,0 °F (> 200,0 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit -

upper (%)

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water)Not available.
Partition coefficient
Not available.

(n-octanol/water)

Auto-ignition temperature > 700 °F (> 371,11 °C)

Decomposition temperatureNot available.ViscosityNot available.Explosive propertiesNot available.Oxidizing propertiesNot available.

9.2. Other information

Percent volatile < 5%Specific gravity 1 - 1,5

SECTION 10: Stability and reactivity

10.1. Reactivity Not available.

10.2. Chemical stability Material is stable under normal conditions. Stable under normal temperature conditions.

10.3. Possibility of hazardous Hazardous polymerization does not occur.

reactions

10.4. Conditions to avoid Temperatures above 100 °C

10.5. Incompatible materials Strong acids, alkalies and oxidizing agents.

10.6. Hazardous Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon

decomposition products dioxide and/or low molecular weight hydrocarbons. Toxic gas.

SECTION 11: Toxicological information

General information Not available. **Information on likely routes of exposure**

Inhalation Health injuries are not known or expected under normal use

Skin contactCauses mild skin irritation. **Eye contact**May be irritating to eyes.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Not available.

11.1. Information on toxicological effects

Acute toxicity Not known. Not classified.

Components Species Test Results

Toluene (CAS 108-88-3)

<u>Acute</u> Dermal

LD50 Rabbit 12120 mg/kg

Oral

LD50 Rat 2,6 g/kg

Skin corrosion/irritation Not classified. **Serious eye damage/eye** Not available.

irritation

Respiratory sensitization Not available.

^{*} Estimates for product may be based on additional component data not shown.

Skin sensitization Not available.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity

Not available.

- single exposure

Specific target organ toxicity

- repeated exposure

Not available.

Aspiration hazard

Mixture versus substance

information

Not available. Not available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Contains a substance which causes risk of hazardous effects to the environment.

Product Species **Test Results**

Crafco Roadsaver Silicone NS Sealant, Roadsaver Silicone SL, Roadsaver Silicone SL Ultra-Low Modulus

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 5,46 - 9,83 mg/l, 48 hr

LC50 Fish Coho salmon, silver salmon

(Oncorhynchus kisutch)

5,5 mg/l, 96 hr

Components Test Results Species

Polydimethylsiloxane (CAS 9016-00-6)

Aquatic

LC50 Fish Channel catfish (Ictalurus punctatus) 2,36 - 4,15 mg/l, 96 hours

Toluene (CAS 108-88-3)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 5,46 - 9,83 mg/l, 48 hours

Coho salmon, silver salmon Fish LC50 8,11 mg/l, 96 hours

(Oncorhynchus kisutch)

12.2. Persistence and

degradability

Not available.

12.3. Bioaccumulative

Not available.

potential

Partition coefficient

n-octanol/water (log Kow)

2,73 Toluene

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil Not available.

12.5. Results of PBT and

Not available.

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects

12.7. Additional information **Estonia Dangerous substances in groundwater Data**

> Toluene (CAS 108-88-3) TOLUENE 0,5 UG/L

TOLUENE 50 UG/L

Estonia Dangerous substances in soil Data

Toluene (CAS 108-88-3) TOLUENE 0,1 MG/KG

> **TOLUENE 100 MG/KG TOLUENE 3 MG/KG**

Material name: Crafco Roadsaver Silicone NS Sealant, Roadsaver Silicone SL, Roadsaver Silicone SL Ultra-Low Modulus 5012 Version #: 01 Issue date: 05-08-2020

^{*} Estimates for product may be based on additional component data not shown.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations.

Not available.

Contaminated packaging Offer rinsed packaging material to local recycling facilities.

EU waste codeWaste codes should be assigned by the user based on the application for which the product was

used. The Waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Disposal Do not dispose of waste into sewer. Dispose in accordance with all applicable regulations.

methods/information

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of Marpol 73/78 and the IBC

Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Toluene (CAS 108-88-3)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Toluene (CAS 108-88-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Toluene (CAS 108-88-3)

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006

On inventory (yes/no)*

SDS EU

National regulations 15.2. Chemical safety

assessment

Not available.

Inventory name

International Inventories

Country(s) or region

		· · · · · · · · · · · · · · · · · · ·
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

SECTION 16: Other information

List of abbreviationsNot available.ReferencesNot available.Information on evaluation
method leading to theNot available.

classification of mixture
Full text of any H-statements
not written out in full under

Sections 2 to 15 H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Revision information Product and Company Identification: Synonyms

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Data

Ecological Information: Ecotoxicity

Transport Information: Product Shipping Name/Packing Group

Regulatory Information: United States HazReg Data: International Inventories

GHS: Classification

Training information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text

Material name: Crafco Roadsaver Silicone NS Sealant, Roadsaver Silicone SL, Roadsaver Silicone SL Ultra-Low Modulus

5012 Version #: 01 Issue date: 05-08-2020 13 / 13

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).