

6165 W Detroit St. • Chandler AZ 85226
 +1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513
 www.crafco.com

READ BEFORE USING THIS PRODUCT

GENERAL SuperSeal AE is a premium asphalt product with mineral fillers and acrylic polymer that is designed to protect and beautify asphalt pavements. SuperSeal AE will help maintain the key properties of the asphalt pavement as well as reduce water penetration leading to longer pavement life. SuperSeal AE can be used on parking lots, streets, residential driveways, airports, etc. Application of Crafco SuperSeal AE is cost effective way to maintain the appearance and increase the longevity of your pavement.

PROPERTIES: SuperSeal AE shall conform to the following properties:

<u>Test</u>	<u>Crafco Recommended Specification</u>
Color (Visual)	SuperSeal AE is jet black upon drying
Drying Time (ASTM D2939)	8 h maximum at 70°F
Non Volatiles (ASTM D2939)	47 – 53%
Ash Content (ASTM D2939)	30 – 60%
Adhesion (ASTM D2939)	Pass
Resistance to Water (ASTM D2939)	Pass
Resistance to Heat (ASTM D2939)	Pass
Flexibility (ASTM D2939)	Pass

Recommended Mix Design

Application	SuperSeal AE		Additive	Aggregate	Application Rate	
	Concentrate	Water			LBS.	Min. Gal.
1 st Seal Coat	100	Gals. 15-20	***	100-500	0.08	0.17
2 nd Seal Coat	100	Gals. 15-20	***	100-500	0.08	0.17

*** Note: SuperSeal AE has 3% Acrylic Latex Hot Blended In During Manufacturing Additional Additives May Be Added If Necessary

INSTALLATION The unit weight of Crafco SuperSeal AE is 9.5 lbs/gal (1.14 kg/l) at 60°F (15.5°C). Prior to use, the user must read and follow Installation Instructions for Superseal AE to verify proper product selection, pavement preparation procedures, application rates, usage precautions and safety procedures. SuperSeal AE must be applied to structurally sound pavement. Any asphalt patching or crack filling should be completed prior to application of SuperSeal AE. SuperSeal AE can be diluted with water to a level not to exceed 20% by volume. Pavements not previously sealed are recommended to have two coats. Application should be suspended if freezing weather or rain is expected within 24 hours.

PACKAGING SuperSeal AE is sold in bulk.

WARRANTY CRAFCO, Inc. warrants that CRAFCO products meet applicable ASTM, AASHTO, Federal or State specifications at time of shipment. Techniques used for the preparation of the cracks and joints prior to sealing or filling are beyond our control as are the use and application of the products; therefore, Crafco shall not be responsible for improperly applied or misused products. Remedies against Crafco, Inc., as agreed to by Crafco, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafco, Inc. All claims for breach of this warranty must be made within three (3) months of the date of use or twelve (12) months from the date of delivery by Crafco, Inc. whichever is earlier. There shall be no other warranties expressed or implied. **For optimum performance, follow Crafco recommendations for product installation.**