



Delivering Confidence Through Innovation, Quality and Value Since 1976

6165 W. Detroit St. • Chandler AZ 85226
1-800-528-8242 • (602) 276-0406 • FAX (480) 961-0513
www.crafco.com

PRODUCT DATA SHEET
**HP ASPHALT COLD
PATCH**

PART NO. 34977

MAY 2020

READ BEFORE USING THIS PRODUCT

GENERAL Crafco HP Asphalt Cold Patch is a black, cold applied, single component, ready to use pavement patching material for repairing potholes, asphalt spalls, cracks and other pavement voids and distresses over 1 inch wide and ½ inch deep. HP Asphalt can be used to repair roads, highways, streets, airport pavements, bridge and parking decks, driveways and walkways. HP Asphalt Cold Patch is specially formulated to be used in all season weather conditions and to adhere in cold and damp pavements. No mixing, heating or special application equipment is required. HP Asphalt Cold Patch develops strength after compaction by tampers, vehicle tires or traffic.

PROPERTIES Properties of Crafco HP Asphalt Cold Patch are as follows:

Workability, (ASTM D6704)	Per Specification
Aggregate Size (ASTM C136)	½ inch maximum
Aggregate Durability (ASTM C131)	40% maximum

APPLICATION It is recommended that the repair area be swept clean of all debris and blown out before Application. Apply HP Asphalt Cold Patch to a height of ½ inch above the area surrounding the hole to be repaired. Do not apply less than 1 inch of material. Deep areas can be filled by adding material after compaction to build thickness, using 1-2 inch material lifts. Compact the material to a level surface with a tamper or vehicle tire. The repair area can be opened to traffic as soon as the compaction is complete. Initial surface tack can be reduced with a light sprinkle application of Portland Cement or calcium carbonate over the compacted surface. Read HP Asphalt Installation Instructions for further information.

PACKAGING HP Asphalt is available in bulk piles and packaged. Packaging consists of individual 50 pound plastic bags which are stacked on standard 48 x 40 pallets. Each pallet contains 60 bags producing a total weight of 3000 pounds. Palletized units are protected from the weather using a three mil thick plastic bag, a weather and moisture resistant cap sheet and a minimum of two layers of six month u.v. protected stretch wrap. Pallets are labeled with the product part number, lot number and net weight. Application Instructions are provided on the bag.

WARRANTY CRAFTCO, Inc. warrants that CRAFTCO products meet applicable specifications at time of shipment. Techniques used for the preparation of the areas to be repaired are beyond our control as are the use and application of the product; therefore, Crafco shall not be responsible for improperly applied or misused product. Remedies against Crafco, Inc., as agreed to by Crafco, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafco, Inc. All claims for breach of this warranty must be made within three (3) months of the dated of use or twelve (12) months from the date of delivery by Crafco, Inc. whichever is earlier. There shall be no other warranties expressed or implied. For optimum performance, follow Crafco recommendations for product installation.