



## PRODUCT DATA SHEET, PART NO. 89037

# ULTRASEAL Primer

March 2012

### DESCRIPTION:

Is a thin penetrating primer consisting of selected asphalt, solvents, and other modifiers blended to meet the requirements of CGSB 37-GP-9Ma.

### USES:

Its intended use is for the priming and sealing of absorbent surfaces and to improve the bonding characteristics of most asphaltic coatings and finishes. Concrete, Asphalt, Masonry, Thermal, Insulation, Roofing Felts and similar surface can be primed with Ultraseal Primer.

### PHYSICAL PROPERTIES:

Color:	Black
Specific Gravity:	0.87
Volume Coverage:	Up to 10 sq. meters per liter or 300-500 ft <sup>2</sup> per gallon based on the porosity of the surface being primed.
Drying Time:	@ 20°C (68°F), 50% R.H. 1 ½ hours touch dry.
Flammability:	Combustible
Application Temperature:	May be applied at low temperatures. Consult Ultraseal Representative.

*The physical and chemical properties are typical average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations.*

### APPLICATION:

Ultraseal 3709 can be applied by spray, brush or roller. Do not allow to puddle or skin over.

### SURFACE PREPARATION:

All surfaces must be dry and free from dust, dirt, grease and any other mater that will inhibit the bonding of the primer.

### LIMITATIONS:

As the primer contains solvents, avoid use near food or other susceptible products or materials. Do not apply on wet, frosted surfaces or to coal tar coatings.

### CLEAN UP:

Use mineral spirits, varsol, asensol or any other suitable solvent.

### CAUTION:

Ultraseal 3709 contains flammable solvents and should be kept away from heat or open flame and should only be used in well ventilated areas.

### PACKAGING:

20 liter pail.

**PERFORMANCE:** Temperature fluctuations, site conditions, surface preparation, traffic, installation technique, material selection, shape factor and surface treatment compatibility influence the effectiveness and useful life of Pavement Preservation treatments. Consider and monitor each element for optimum results. Purchaser and end user should determine applicability for use in their specific conditions.

**WARRANTY:** CRAFCO, Inc. warrants that CRAFCO products meet applicable ASTM, AASHTO, Federal or State specifications at time of shipment. Techniques used for the preparation of the cracks and joints prior to sealing or filling are beyond our control as are the use and application of the products; therefore, Crafcoc shall not be responsible for improperly applied or misused products. Remedies against Crafcoc, Inc., as agreed to by Crafcoc, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafcoc, Inc. All claims for breach of this warranty must be made within three (3) months of the date of use or twelve (12) months from the date of delivery by Crafcoc, Inc. whichever is earlier. There shall be no other warranties expressed or implied. **For optimum performance, follow Crafcoc recommendations for product installation.**



6165 W. Detroit Street • Chandler AZ 85226  
1-800-528-8242 • (602) 276-0406 • Fax (480) 961-0513  
www.crafcoc.com