

6165 W Detroit St. • Chandler AZ 85226
+1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513
www.crafco.com

READ BEFORE USING THIS PRODUCT

GENERAL

Action Pave Asphalt Tack Coat is 100% anionic asphalt (bitumen) emulsion that meets DOT standards for SS-1h and ASTM D977, Standard Specification for Emulsified Asphalt. Action Pave Tack Coat is designed to create a fresh bond between existing pavement and a new bonded repair that prevents potholes, cracks, and pavement distresses.

RECOMMENDED USES

Action Pave Asphalt Tack Coat is designed for use as a tack coat for hot and cold mix patching and other various uses where improved adhesion is desired.

SPECIFICATION CONFORMANCE

Action Pave Asphalt Tack Coat complies with ASTM D977 Type SS-1h.

INSTALLATION

- **Application**
 - May be sprayed, rolled, hand squeegeed or brushed on. Most sprayers work. Product is ready to use, do not dilute.
- **Coverage**
 - One (1) coat application typically is 80 – 260 square feet per gallon, depending on surface porosity and method of application. Apply tack coat for patching at 0.05 – 0.1 g/sy.
- **Surface Preparation**
 - Surface must be cleaned of dust, dirt, and debris.

LIMITATIONS

- Do not apply when surface temperature is below 50 °F (10 °C) or when surface temperature is above 130 °F (55 °C).
- Do not apply when rain, fog or high humidity is imminent.

PACKAGING AND AVAILABILITY

5 Gal. (18.9 L) pails.

STORAGE

- Close cover tightly
- Do not store in direct sunlight.
- Keep from freezing
- Storage temperature range 40 – 90 °F.
- Dispose of in accordance with state and federal regulations

WARRANTY

ACTION PAVE® Asphalt Tack Coat is warranted by the manufacturer to meet specification requirements at time of shipment. Techniques used for pavement preparation prior to Action Pave Asphalt Tack Coat application are beyond manufacturer control as are use and application of Action Pave Asphalt Tack Coat; therefore, the manufacturer shall not be responsible for improperly applied or misused Action Pave Asphalt Tack Coat. Remedies against the manufacturer are limited to replacing nonconforming product or refund (full or partial) of purchase price. All claims for breach of this warranty must be made within three (3) months of delivery date. There shall be no other warranties expressed or implied. **For optimum performance, follow recommendations for Action Pave installation.**

No informal dispute mechanism has been established. Notice must be given in writing to Crafcoc, Inc 6165 W. Detroit St., Chandler, AZ 85226. A sample of the product claimed defective must be retained together with satisfactory proof of purchase. No claim will be honored if the lot number(s) are not provided therewith. THIS WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES AND EXPRESSLY EXCLUDES ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR PARTICULAR PURPOSE, AS WELL AS LIABILITY FOR CONSEQUENTIAL DAMAGES. Crafcoc Sales or Technical Representatives have no authority to extend any guarantee beyond that outline above.