

## 1. Identification

<b>Product identifier</b>	<b>Anti-Spall 50/50</b>
<b>Other means of identification</b>	None.
<b>Recommended use</b>	Concrete Cure.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Manufacturer:</b>	Crafco, Inc.
<b>Address:</b>	6165 West Detroit St. Chandler, AZ 85226 USA
<b>Contact Name:</b>	Crafco Materials Engineering
<b>Telephone:</b>	602-276-0406
<b>E-mail:</b>	sales@crafco.com
<b>CHEMTREC:</b>	800-424-9300 (North America) + 1-703-527-3887 (International)

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Flammable liquid and vapor. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.
<b>Precautionary statement</b>	
<b>Prevention</b>	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
<b>Response</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. Call a POISON CENTER or doctor/physician if you feel unwell. In case of fire: Use appropriate media for extinction. Specific treatment (see this label).
<b>Storage</b>	Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** Combustible.

**Supplemental information** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		64742-47-8	15 - 35
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.		64742-88-7	15 - 35
XYLENE (MIXED)		1330-20-7	1 - 10
Other components below reportable levels			50

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth thoroughly. Give victim water or milk. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Never give anything by mouth to a victim who is unconscious or is having convulsions. Get medical attention if symptoms occur.

**Most important symptoms/effects, acute and delayed** Direct contact with eyes may cause temporary irritation.

**Indication of immediate medical attention and special treatment needed** Treat symptomatically.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Get medical attention if symptoms occur.

### 5. Fire-fighting measures

**Suitable extinguishing media** Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical** During fire, gases hazardous to health may be formed. Carbon monoxide and carbon dioxide.

**Special protective equipment and precautions for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Fire fighting equipment/instructions** Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** Combustible.

### 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not breathe mist or vapor. Do not touch or walk through spilled material. Vapor accumulation may reach explosive concentrations if airflow to location is inadequate. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS. Keep people away from and upwind of spill/leak.

**Methods and materials for containment and cleaning up**

Never return spills to original containers for re-use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area).

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Remove with vacuum trucks or pump to storage/salvage vessels. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage****Precautions for safe handling**

This product contains drying oils; when a combustible media (rags, flammable absorbent, etc.) is soaked in this product, the drying oils may cause spontaneous combustion if these materials are disposed of improperly. If heated, irritating vapors may be formed. Avoid prolonged exposure. Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Provide adequate ventilation. Wash thoroughly after handling. Avoid release to the environment.

**Conditions for safe storage, including any incompatibilities**

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Prevent electrostatic charge build-up by using common bonding and grounding techniques. Keep out of the reach of children.

**8. Exposure controls/personal protection****Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS 64742-88-7)	PEL	400 mg/m <sup>3</sup>
		100 ppm
XYLENE (MIXED) (CAS 1330-20-7)	PEL	435 mg/m <sup>3</sup>
		100 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS 64742-88-7)	TWA	200 mg/m <sup>3</sup>	Non-aerosol.
XYLENE (MIXED) (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)	TWA	100 mg/m <sup>3</sup>
XYLENE (MIXED) (CAS 1330-20-7)	STEL	655 mg/m <sup>3</sup>
		150 ppm
	TWA	435 mg/m <sup>3</sup>
		100 ppm

## Biological limit values

### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
------------	-------	-------------	----------	---------------

XYLENE (MIXED) (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
--------------------------------	---------	----------------------	---------------------	---

\* - For sampling details, please see the source document.

## Exposure guidelines

### US ACGIH Threshold Limit Values: Skin designation

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS Can be absorbed through the skin. 64742-88-7)

### Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible). A full face respirator is recommended.

#### Skin protection

##### Hand protection

Wear appropriate chemical resistant gloves.

##### Other

Wear appropriate chemical resistant clothing. Wear eye/face protection.

#### Respiratory protection

A full face respirator is recommended for eye protection and respiratory protection when applying product using conventional sprayers.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Keep away from food and drink.

## 9. Physical and chemical properties

### Appearance

Transparent Amber Liquid.

#### Physical state

Liquid.

#### Form

Liquid.

#### Color

Amber.

### Odor

Linseed Oil. Petroleum Solvent.

### Odor threshold

Not available.

### pH

Not available.

### Melting point/freezing point

Not available.

### Initial boiling point and boiling range

350.6 °F (177 °C)

### Flash point

104.0 °F (40.0 °C)

### Evaporation rate

Not available.

### Flammability (solid, gas)

Not applicable.

### Upper/lower flammability or explosive limits

#### Explosive limit - lower (%)

Not available.

#### Explosive limit - upper (%)

Not available.

### Vapor pressure

Not available.

### Vapor density

> 1 (1 = air)

### Relative density

Not available.

### Solubility(ies)

#### Solubility (water)

Not available.

### Partition coefficient (n-octanol/water)

Not available.

### Auto-ignition temperature

Not available.

### Decomposition temperature

Not available.

<b>Viscosity</b>	130 cP @25°C
<b>Other information</b>	
<b>Density</b>	7.10 - 7.30 lb/gal
<b>Percent volatile</b>	45 - 50 %
<b>Specific gravity</b>	0.851 - 0.875
<b>VOC</b>	400 g/l

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Strong oxidizing agents. Strong acids. Contact with alkalis. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong acids. Alkalis.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause drowsiness and dizziness.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

**Acute toxicity** Not known.

Components	Species	Test Results
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS 64742-88-7)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	61 mg/l, 4 Hours
XYLENE (MIXED) (CAS 1330-20-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 43 g/kg
<b>Inhalation</b>		
LC50	Rat	6350 mg/l, 4 Hours

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

### Respiratory or skin sensitization

<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

### Carcinogenicity

#### IARC Monographs. Overall Evaluation of Carcinogenicity

XYLENE (MIXED) (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

<b>Reproductive toxicity</b>	Not classified.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects
<b>Further information</b>	This product has no known adverse effect on human health.

**12. Ecological information**

**Ecotoxicity** Toxic to aquatic life. The product contains a substance which may cause long-term adverse effects in the aquatic environment.

Product	Species	Test Results	
Anti-Spall 50/50			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	15.3815 mg/l, 48 hours estimated
Fish	LC50	Fish	8.9743 mg/l, 96 hours estimated
<b>Components</b>			
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (CAS 64742-88-7)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours
XYLENE (MIXED) (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

XYLENE (MIXED) 3.12 - 3.2

**Mobility in soil** Not expected to be mobile in soil.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal instructions** If discarded, this product is considered a RCRA ignitable waste, D001. Empty drum liners retain residue that will burn and can be dangerous. Keep away from heat, sparks, flames, static electricity or other sources of ignition. Liners should be emptied of contents and segregated from liners containing other products. Dispose of empty liners in an environmentally safe manner in accordance with governmental regulations. Do not reuse liners for any purpose. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. Do not allow this material to drain into sewers/water supplies.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company. D001: Waste Flammable material with a flash point <140 F
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material including paint thinning, drying, removing, or reducing compound
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	III
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	B1, B52, IB3, T2, TP1, TP29
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	173
<b>Packaging bulk</b>	242

### IATA

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material (including paint thinning or reducing compounds)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

### IMDG

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound), MARINE POLLUTANT
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	Yes
<b>EmS</b>	F-E, <u>S-E</u>
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.


DOT



IATA; IMDG



Marine pollutant



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

XYLENE (MIXED) (CAS 1330-20-7) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**SARA 302 Extremely hazardous substance**

Not listed.

**Classified hazard categories**

Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Specific target organ toxicity (single or repeated exposure)

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
XYLENE (MIXED)	1330-20-7	1 - 10

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

XYLENE (MIXED) (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.



**Safe Drinking Water Act (SDWA)** Not regulated.

## US state regulations

### California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)

XYLENE (MIXED) (CAS 1330-20-7)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 05-25-2021

**Revision date** 08-27-2021

**Version #** 02

**NFPA ratings**  
Health: 1  
Flammability: 2  
Instability: 0

**Disclaimer** Crafcro, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information** Product and Company Identification: Product and Company Identification