SAFETY DATA SHEET



1. Identification

Product identifier Ultraseal Hot Applied Sealants

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Crafco, Inc.

Address: 6165 West Detroit St.

Chandler, AZ 85226 USA

Contact Name: Crafco Materials Engineering

Telephone: 602-276-0406 **E-mail:** sales@crafco.com

CHEMTREC: 800-424-9300 (North America)

+ 1-703-527-3887 (International)

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements

Hazard symbol None.

Signal wordNot applicable. **Hazard statement**Not applicable.

Precautionary statement

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	20 - 100
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	0 - 40
Other components below reportable	e levels		49.39

Other components below reportable levels

.. .

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention, if needed. Call a physician if symptoms develop or persist.

Material name: Ultraseal Hot Applied Sealants
5980 Version #: 02 Revision date: 05-29-2020 Issue date: 05-27-2015

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes

before reuse.

Not available.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO

NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and

persists

Ingestion Rinse mouth. Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the

substance. Call a POISON CENTER or doctor/physician if you feel unwell.

Most important

symptoms/effects, acute and delayed

In case of ingestion, the decision of whether or not to induce vomiting should be made by the attending physician. Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

Indication of immediate medical attention and special treatment needed

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Addition of water or foam to the fire may cause frothing.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases. Development of hazardous combustion gases or vapours possible in the event of a fire. The following may develop: Acrolein.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. By fire, toxic gases may be formed (COx, NOx). Keep run-off water out of sewers and water sources. Dike for water control.

Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Do not touch or walk through spilled material

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Dike far ahead of spill for later disposal. Following product recovery, flush area with water.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Runoff or release to sewer, waterway or ground is forbidden.

7. Handling and storage

Precautions for safe handling

The product is non-combustible. If heated, irritating vapors may be formed. Do not use in areas without adequate ventilation. Wash hands thoroughly after handling. Wash hands after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep the container tightly closed and dry. Store in a closed container away from incompatible materials. Keep out of the reach of children.

SDS US

Material name: Ultraseal Hot Applied Sealants

5980 Version #: 02 Revision date: 05-29-2020 Issue date: 05-27-2015 2 / 7

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

ComponentsTypeValueFormDISTILLATES
(PETROLEUM),PEL5 mg/m3Mist.

HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

US. ACGIH Threshold Limit Values

ComponentsTypeValueFormASPHALT (CAS 8052-42-4)TWA0.5 mg/m3Inhalable fume.DISTILLATES
(PETROLEUM),TWA5 mg/m3Inhalable fraction.

HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)

US. NIOSH: Pocket Guide to Chemical Hazards

Form Value Components Type ASPHALT (CAS 8052-42-4) Ceiling 5 mg/m3 Fume. **DISTILLATES** Ceiling 1800 ma/m3 (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5) **STEL** 10 mg/m3 Mist. **TWA** 350 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible). Wear chemical goggles; face shield

(if handling molten material).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear suitable protective clothing and eye/face protection. Use of an impervious apron is

recommended.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards During product use, there is a risk of thermal burns.

General hygiene When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Keep away from food considerations and drink. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance Solid.
Physical state Solid.
Form Solid.

Color Black. Dark brown

Odor Product is a black, semi-solid with a burnt tar odor.

Odor threshold Not available.

pH Not available.

Melting point/freezing point 150 - 250 °F (65.56 - 121.11 °C) ASTM D36 Softening Point

Material name: Ultraseal Hot Applied Sealants

SDS US

Initial boiling point and

boiling range

> 800 °F (> 426.67 °C)

Flash point

> 400.0 °F (> 204.4 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Not available. Vapor pressure Vapor density Not available. **Relative density** Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available. (n-octanol/water)

Auto-ignition temperature

> 700 °F (> 371.11 °C)

Decomposition temperature Not available. Not available. **Viscosity**

Other information

Density Not Available

Percent volatile 0 %

1.00 - 1.90 Specific gravity

10. Stability and reactivity

Reactivity Not available.

Chemical stability Material is stable under normal conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Conditions to avoid Strong oxidizing agents.

Incompatible materials Incompatible with oxidizing agents.

Hazardous decomposition Upon decomposition, product emits acrid dense smoke with carbon dioxide, carbon monoxide, trace

oxides of nitrogen and sulfur, and water. products

11. Toxicological information

Information on likely routes of exposure

Inhalation May be harmful if inhaled. However, this product does not currently meet the criteria for

classification.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not classified.

Skin corrosion/irritation Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Material name: Ultraseal Hot Applied Sealants 5980 Version #: 02 Revision date: 05-29-2020 Issue date: 05-27-2015 Serious eye damage/eye

irritation

Not classified.

Respiratory or skin sensitization

Respiratory sensitization Not classified. **Skin sensitization** Not classified.

Germ cell mutagenicity Non-mutagenic based on Modified Ames Assay.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityContains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

Not classified.

- repeated exposure

Aspiration hazard Not classified.

Chronic effects Prolonged or repeated contact may cause drying, cracking, or irritation of the skin

12. Ecological information

EcotoxicityThis product has no known eco-toxicological effects. Not expected to be harmful to aquatic

organisms.

Persistence and degradabilityNot available.Bioaccumulative potentialNot available.Mobility in soilNot available.Other adverse effectsNot available.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261.

Hazardous waste code Not applicable.

Waste from residues /

unused products

Dispose of in accordance with local regulations.

Contaminated packaging Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

General information Not regulated as dangerous goods.

Further information If the product is shipped at temperatures below 212°F (100°C), it is not regulated for transport by

ground, air or vessel. If shipped above 212 deg F: "UN3257, Elevated Temperature Liquid, n.o.s.

(Asphalt mixture), 9, PG III"

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

Material name: Ultraseal Hot Applied Sealants

SDS US

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

T.....

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 05-27-2015 **Revision date** 05-29-2020

Version # 02

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 0

Flammability: 0 Instability: 0

5980 Version #: 02 Revision date: 05-29-2020 Issue date: 05-27-2015

O-- !------ (---- /---*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

References ACGIH

EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Revision information

Product and Company Identification: Product and Company Identification

First-aid measures: Skin contact

Exposure controls/personal protection: Appropriate engineering controls

HazReg Data: International Inventories

Material name: Ultraseal Hot Applied Sealants

5980 Version #: 02 Revision date: 05-29-2020 Issue date: 05-27-2015 7 / 7

SDS US