

6165 W Detroit St. • Chandler AZ 85226
+1 (602) 276-0406 • +1 (800) 528-8242 • FAX +1 (480) 961-0513
www.crafco.com

Sealant product shall be supplied in approximately 30 pound (13.6 kg) completely meltable packages that are interlocked stacked on pallets containing approximately 65 packages / 1950 pounds (885 kg) of product or 70 packages / 2100 pounds (952 kg) depending on location of manufacture. Packages are enclosed in a corrugated container. The packages and palletized unit shall be water and weather resistant so that outside storage is permissible.

Individual packages consist of one (1) to three (3) blocks which are partially wrapped in a block liner. The blocks are wrapped in a shrink wrap to form a package. Each package has a printed fully meltable label in accordance with OSHA, GHS and ASTM requirements. The individual packaging shall quickly melt into the product at normal sealant melt temperatures without affecting product installation characteristics or specification conformance and not be more than 0.50% of the product weight.

NoBox sealant products are sold by the pallet only and individual packages are not intended or labeled for individual sale.

The packaging shall have the following properties:

Block Liner	
Thickness (ASTM D1777)	0.0015 inches (0.38 mm) minimum
Package Shrink Wrap	
Thickness	100 gauge
Corrugated Container	
Double Walled	
Burst Strength	275 lb/in ² (1.90 MPa) minimum