

AE Sealcoat



Black Beauty, Green Tech

Crafco AE sealcoat is an asphalt emulsion sealcoat offering both protection and beautification in a nonhazardous, environmentally friendly formula. It gives you the same rich, black finish as traditional sealcoats and the same protection against damaging elements – without the odor, hazardous fumes or skin irritation during installation. AE cleans up easily with water and significantly reduces accidental staining on non-pavement surfaces. AE can also be used in areas with coal tar bans or similar restrictions.

BENEFITS

- Pleasing black finish**
- Outstanding durability**
- Minimal odor with no skin irritation**
- Meets or exceeds relevant specs**





Eco-Friendly Sealcoat Protection

FEATURES

Rich black finish

Fast dry and cure time

Water cleanup

Available in concentrate, ready mix, sand mix and sand ready mix

Low VOC (<10 g/L)

Meets or exceeds ASTM, AASHTO and FAA specifications



Scan this QR code to view all of Crafcó's material documentation.

Asphalt emulsion products don't require a petroleum solvent, so Crafcó AE gives off minimal odor and fewer VOC and PAH gases than traditional sealcoats. AE provides reliable protection on par with industry standards whether applied to home driveways, airport runways or anything in between.

Crafcó AE sealcoat is available in three grades for different applications

AE Elite contains asphalt, minerals, latex polymers and other additives to provide outstanding damage resistance with long-lasting visual appeal. Reapplication is suggested every 2-4 years, offering contractors, agencies and property owners a cost-effective solution to protect a variety of paved surfaces.

AE Ultimate doubles our proprietary polymer blend, extending protection up to 6 years and adding extra resistance against damaging chemicals from leaking vehicles. Ultimate is the most durable option for the most demanding environments.

AE Stealth is exclusively for airports and is formulated to meet FAA Specification P631. Stealth eliminates the need for on-site additive mixing and minimizes water dilution for easy application and optimal film thickness. Given the rigorous demands of airports, we recommend reapplying Stealth every 2-3 years for runway sections and every 3-4 years for non-runway sections.

©March 2025 Crafcó, Inc.