



+1 (602) 276-0406
www.crafco.com

PRODUCT DATA SHEET

ACTION PAVE® ASPHALT TACK COAT

PART NUMBER 11965

AUGUST 2026

READ BEFORE USING THIS PRODUCT

GENERAL

Action Pave Asphalt Tack Coat part number 11965 is 100% anionic asphalt (bitumen) emulsion that meets DOT standards for SS-1h and ASTM D977, Standard Specification for Emulsified Asphalt. Action Pave Tack Coat is designed to create a fresh bond between existing asphalt pavement and a new bonded repair for potholes, cracks, and pavement distresses.

RECOMMENDED USES

Action Pave Asphalt Tack Coat is designed for use as a tack coat for hot and cold mix patching and other various uses where improved adhesion is desired.

SPECIFICATION CONFORMANCE

Action Pave Asphalt Tack Coat complies with ASTM D977 Type SS-1h.

INSTALLATION

- **Application**
 - May be sprayed, rolled, hand squeegeed or brushed on. Most sprayers work. Product is ready to use, do not dilute.
- **Coverage**
 - One (1) coat application typically is 80 – 260 square feet per gallon, depending on surface porosity and method of application. Apply tack coat for patching at 0.05 – 0.1 g/sy.
- **Surface Preparation**
 - Surface must be cleaned of dust, dirt, and debris.

LIMITATIONS

- Do not apply when surface temperature is below 50 °F (10 °C) or when surface temperature is above 130 °F (55 °C).
- Do not apply when rain, fog or high humidity is imminent.

PACKAGING AND AVAILABILITY

5 Gal. (18.9 L) pails.

STORAGE

- Close cover tightly
- Do not store in direct sunlight.
- Keep from freezing
- Storage temperature range 40 – 90 °F.
- Dispose of in accordance with state and federal regulations

WARRANTY

This product is warranted by the manufacturer to meet specification requirements at time of shipment according to Crafco terms and conditions of sale. For optimum performance, follow recommendations for installation.